

CERTIFICATE OF COMPLIANCE

Certificate Number 20191126-R26797
Report Reference R26797-20170727
Issue Date 2019-NOVEMBER-26

Issued to: SALTO SYSTEMS S L
POL. LANBARREN. ARKOTZ 9
20180 OIARTZUN SPAIN

**This certificate confirms that
representative samples of**

ELECTRICALLY CONTROLLED SINGLE-POINT LOCKS
AND LATCHES

Refer to addendum for models

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety:

ANSI/UL 10C - Positive Pressure of Fire Tests of Door
Assemblies.

ANSI/UL 10B - Fire Tests of Door Assemblies

CAN/ULC-S104-15 - Standard Method for Fire Tests of
Door Assemblies

Additional Information:

See the UL Online Certifications Directory at
<https://iq.ulprospector.com> for additional information.

This *Certificate of Compliance* does not provide authorization to apply the UL Mark. Only the UL Follow-Up Services Procedure provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20191126-R26797
Report Reference R26797-20170727
Issue Date 2019-NOVEMBER-26

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Model No. Salto LA1T Series Mortise electrically controlled single point lock with an AFi/AFxx Series Reader Assembly (Commercial name ÆElement Fusion). These lock sets may be provided with a 3/4 in. (19 mm) latchbolt and a 2 3/8 in. (60 mm) or 2-3/4 in. (70 mm) backset. For use on wood doors rated up to and including 3/4 h, composite doors rated up to and including 1-1/2h and metal doors rated up to and including 3h. Wood and composite door required the minimum thickness of the door tested for the installation of this hardware.



Bruce Mahrenholz, Director North American Certification Program

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/about/locations/>

