

# SKG-IKOB PRODUCTCERTIFICATE

## 440.632.01

Date of issue: 29-01-2024



### Certificate holder

Salto Systems SL  
Poligono Lanbarren C / Arkotz 9  
920180 Oiartzun  
T: +34 (0) 943 344 550  
E: info@saltosystems.com  
I: www.saltosystems.com



### Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

**narrow plate with electro mechanical handle link non lockable**

delivered under logo / brand:

**SALTO**

delivered under type- and / or article number:

**Ei4K0 m 00 ff t 8 h r , Ei450 m 00 ff c t s r S , Ei850 m 00 ff c t s r S**

meets class 2 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

CERTIFICATE

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
info@skgikob.nl  
www.skgikob.nl

# SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL  
Number: 440.632.01

page 2 of 2

## 1. PRODUCT

narrow plate with electro mechanical handle link non lockable

## PRODUCT TYPE

security furniture

## 2. TECHNICAL SPECIFICATION

Operating:	Mechanical and electrical operation
Construction:	1 set of an outside part with electro mechanical handle link and an inside part with mounting screws
System:	with OR without 17 mm PC hole various handles or turn-knobs
	operation by: - Keycard, Fob or Wearable - SALTO KS mobile app. on phone or tablet
Material:	outside part: inox with aluminium and zinc coated steel inside inside part: zinc coated steel with inox cover
Dimension:	outside- /inside part: 282x41x20 mm
Fixing:	3xM5 in steel cams
Intended use:	wood, PVC, metal
	The electromechanical product is operated electronically using the options stated under "System". The operating options listed below, as well as the closure, are included in the Self-declaration - additional product requirements for electromechanical and electronic hinges and locks; dated 08-01-2024, with which the certificate holder declares that the applicable requirements are met.
	in combination with (self clothing) mortice locks

## 3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:

Algemeen: 201155-ED.08032023  
SKG: 220744 - ED2 -08032023  
SKG: 226907 - ED.-14-03-2023  
SKG: 226906 - ED2.14-06-2022

## 4. PERFORMANCES

A narrow plate with electro mechanical handle link non lockable according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this narrow plate with electro mechanical handle link, non lockable is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 2 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this narrow plate with electro mechanical handle link, non lockable is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).