

# SKG-IKOB PRODUCTCERTIFICATE

## 440.393.06

Date of issue: 29-01-2024



### Certificate holder

Salto Systems SL  
Poligono Lanbarren C / Arkotz 9  
920180 Oiartzun  
T: +34 (0) 943 344 550  
E: info@saltosystems.com  
I: www.saltosystems.com



### Declaration of SKG-IKOB

This certificate has been issued on the basis of BRL 3104 in accordance with the SKG-IKOB Regulations for Attestation, Certification and Inspection.

SKG-IKOB declares that the by or on behalf of the certificate owner produced building hardware product:

### Europrofile cylinder electro mechanical

delivered under logo / brand:

### SALTO

delivered under type- and / or article number:

### NME1xxG , NME3xxG , NJE1xxG , NJE3xxG

meets class 3 STER according BRL 3104 and NEN 5089: 2009 if the product is indelibly marked with the SKG mark, as shown above.

For SKG-IKOB

A handwritten signature in blue ink, consisting of a stylized, cursive script.

ir. H.A.J. van Dartel  
Certification manager

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this certificate is still valid and actual.  
This certificate contains 2 pages.

SKG-IKOB Certificatie  
Poppenbouwing 56  
4191 NZ Geldermalsen

Postbus 202  
4190 CE Geldermalsen

T 088-2440100  
[info@skgikob.nl](mailto:info@skgikob.nl)  
[www.skgikob.nl](http://www.skgikob.nl)

CERTIFICATE

# SKG-IKOB PRODUCTCERTIFICATE

Salto Systems SL  
Number: 440.393.06

page 2 of 2

## 1. PRODUCT

Europrofile cylinder electro mechanical

## PRODUCT TYPE

cylinder

## 2. TECHNICAL SPECIFICATION

Operating:	Electronical operation
Construction:	single with a lockable knob double with on both sides a lockable knob modulair single with a lockable knob modulair double with on both sides a lockable knob
System:	knob with full length plug, coupled with de cam by electronic operation  operation by: - Keycard, Fob or Wearable - SALTO KS mobile app. on phone or tablet
Material:	cylinder body: brass with various coatings with OR without steel bridge
Dimension:	17 mm profile from: (single) 10/30 mm and (double) 30/30 mm in various extensions per 5 mm possibly with extended plug of +5 OR +10 mm
Fixing:	1 steel bolt M5, length $\geq$ backset + 10 mm
Intended use:	The electromechanical product is operated electronically using the options stated under "System". The operating options listed below, as well as the closure, are included in the Self-declaration - additional product requirements for electromechanical and electronic hinges and locks; dated 08-01-2024, with which the certificate holder declares that the applicable requirements are met.  in combination with cylinder mortise locks and security furniture

## 3. DELIVERY

The preconditions for correct installation and the fasteners to be used are described in the enclosed or digitally published installation instructions with the following version:

225790-ED.1- 12/09/2023

227823 -ED0 -23/05/2023

## 4. PERFORMANCES

A Europrofile cylinder electro mechanical according this certificate fulfils the relevant requirements of BRL 3104.

A window- or door set, in which this Euro-profile cylinder, electro mechanical is installed according the installation instructions of the certificate holder meets at least burglar resistance class (RC) 3 of NEN 5096 and EN 1627, if:

the façade element or the (profile-)system from which the element is manufactured is delivered under a (KOMO-)quality approval with respect to the aspect burglar resistance, in which the actual window or door type is admitted and the herein mentioned conditions are fulfilled.

A window or door, in existing buildings, in which this Euro-profile cylinder, electro mechanical is installed according the installation instructions of the certificate holder, meets the requirements of the Police Mark Save Housing (PKVW) - Existing Building, if:

the other aspects of the façade element also comply with the applicable PKVW Protection directive (publication CCV).